

In order to utilize the ProjectWise Explorer V8i (Windows Thick Client) you need to have port 5800 open inbound and outbound on any firewall that the users must traverse to access the Internet. This port must be open for both incoming and outgoing communications.

Next you will need to download and install the ProjectWise Explorer 08.11.07.107 software from CP&Y's ftp site: <ftp://software.cpyi.com:cpysoftware@ftp.cpyi.com>

If you already have Projectwise installed, compatible version that will work with our datasource are versions 08.11.xx.xxx

If you have the XM version of Projectwise XM installed, you will need to uninstall it first, or during the setup for the V8i Installation you will need to give it an alternate install path (c:\program files\bentley\projectwiseV8i)

The users that will be accessing the CP&Y ProjectWise environment will need CP&Y Projectwise user account which can be requested through a CP&Y Project Manager or through emailing supportcenter@cpyi.com

Once Projectwise has been installed, go into the control panel of your computer, and open up your Projectwise Network Settings. You will need to make sure you are an administrator on the computer to perform the next step.

Go to the DNS Services tab, and add CPYI as the name, then pwwgate.cpyi.com as the Host/IP, and 5800 as the Port, then click the Add button. Next click on the Datasource Listing and reenter the same information there as well. Once done, hit ok to exit out of the ProjectWise Network Configuration Settings.

Now you should be able to open up the Projectwise Explorer V8iClient and logon to the CPYI datasource with your supplied credentials.